



CRITERIA	RESULT
FILTR TYPE	DIESEL
SHAPE & DIMENSIONS OF FILTER	NET
MATERIAL OF THE NET	PA6.6 Monofilament
AREA (cm ²)	20.2 ±10%
THICKNESS NET, mm	0.13
MESH OPENING (0.113x0.204) (mm ²)	0.0231
NOMINAL FLOW (L/H)	25
HOUSING MATERIAL	POLYAMIDE

Test Requirements:
1. Testing pressure for leakage: 3 BAR
2. Burst Pressure: 4 BAR
3. Temp. Range: +100 °C - -40°C
4. Filtration Area : 20.2 SQcm
5. Mesh Opening: 0.113 x 0.204 mm

All the dimensions are in mm and REF.

Itemref	Quantity	Title/Name, designation, material, dimension etc			Article No./Reference	
Designed by Shvartsman	Checked by Shvartsman	Approved by - date 13/03/05	Filename 202018D	Date 13/03/05	Scale 1:1	
 GUR Filter Co. Ltd. AUTOMOTIVE FUEL FILTER 12, Kamenyaya Str. Industrial Zone, Herson Tel: 978-5-500305 Fax: 978-5-500305				GF-2018D		
FUEL FILTER				Edition a	Sheet 1/1	N